

HC 403 PVC Tape

PRODUCT DATA SHEET



CONSTRUCTION

Substrate: 3.2-mil Embossed PVC
Adhesive: Acrylic
Liner: 40-lb Kraft

FEATURES

- Acrylic based adhesive
- Performs well in challenging environmental conditions
- Resistant to many chemicals
- White

TYPICAL USES

- Sealing PVC jacketing and fitting covers on mechanical insulation

TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Thickness	0.005-in	0.127-mm	PSTC-133
Peel Adhesion to Stainless Steel	20-oz/in	2.2-N/cm	PSTC-101
Tensile Strength	15-lbs/in	26-N/cm	PSTC-131
Elongation	200%	200%	PSTC-131

APPLICATION

Application surface must be clean, dry and free of contaminants.

SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
1-in	108-ft	48	27
1.5-in	108-ft	32	27
2-in	108-ft	24	27

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 1.4.2010 13:45.