

HC 801 Transfer Tape

PRODUCT DATA SHEET



CONSTRUCTION

Adhesive: 2.5-mil Acrylic
Liner: 60-lb Silicone Coated Kraft

FEATURES

- SSL transfer tape
- Aggressive rubber adhesive system
- Bonds well over a wide range of environmental conditions
- Bonds well to irregular and rough surfaces

COMMON USES

- Seal vapor retarder or facing overlap seams on mechanical and other types of insulation

TYPICAL PROPERTIES

Test	Typical Values (English)	Typical Values (metric)	Test Method
Total Thickness without Liner	0.0025-in	0.0635-mm	PSTC-133
Peel Adhesion to Stainless Steel	60-oz/in	17-N/25mm	PSTC-101

APPLICATION

Application surface must be clean, dry and free of contaminants.

SHELF LIFE & STORAGE

Under ideal storage conditions of 60°F to 80°F and low humidity, shelf life is one year from date of purchase.

STANDARD CONFIGURATIONS & PACKAGING (CUSTOM CONFIGURATIONS & PACKAGING AVAILABLE UPON REQUEST)

Roll Width	Roll Length	Rolls/Carton	Cartons/Pallet
1-in	180-ft	48	27
1.5-in	180-ft	32	27
2-in	180-ft	24	27

Physical and performance values and characteristics shown above are obtained through recommended test procedures. The above values do not represent a guarantee of product performance. Values represent nominal and average values; individual roll values may vary from average values indicated on the data sheet. User is responsible for determining suitability and fitness for use. Revision 8.15.2011 13:29.